



This is to certify that: Architectural Windows Ltd

Unit 16, Midas Business Centre

Wantz Road Dagenham **RM10 8PS** United Kingdom

Holds Certificate Number: KM 673813

In respect of:

**BS 4873 Aluminium Window Fabricator** 

This issues the right and licence to use the Kitemark in accordance with the Kitemark Terms and Conditions governing the use of the Kitemark, as may be updated from time to time by BSI Assurance UK Ltd (the "Conditions"). All defined terms in this Certificate shall have the same meaning as in the Conditions.

The use of the Kitemark is authorized in respect of the Product(s) detailed on this Certificate provided at or from the above address.

For and on behalf of BSI: Gary Fenton, Global Product Certification Director

First Issued: 2017-08-09 Latest Issue: 2017-08-09

Page: 1 of 11

...making excellence a habit.™



No. KM 673813

#### BS 4873:2009 - Aluminium Alloy Windows and Doorsets.

This Certificate covers the fabrication of windows from the range of profiles and components supplied by The Parkside Group Ltd under Certificate Number KM 578159.

System(s): **Comar 5Pi Aluminium Alloy Window System** 

**Fabrication and** Installation:

Fabricated and installed in accordance with the latest issue(s) of the following

Comar Architectural Aluminium Systems controlled documentation:

Comar 5Pi Window System Technical Manual

The windows are internally glazed only, double glazed only, multipoint locking **System description:** 

only with mechanically fixed transoms/mullions

**Ventilation:** None

**Window Types:** Tilt/turn windows

Multilight windows comprising opening light(s) and/or fixed light(s)

First Issued: 2017-08-09 Latest Issue: 2017-08-09

Page: 2 of 11

No. KM 673813

### **Comar 5Pi Aluminium Alloy Window System**

### **Size Limitations and Performance characteristics**

Window Type	Width (mm) - Maximum	Height (mm) - Maximum	Area(m²) - Maximum	Transom/Mullion Length (mm) inc frame - Maximum	Air Permeability classification	Watertightness classification	Resistance to Wind classification	Exposure category as given in Table 1 of BS 6375-1:2009 (except*)
Sash dimensions for appr	oved tilt/t	urn sash p	orofiles:					
Tilt/turns	1100	1600	-	-	4	7A	2400	2400*
Overall dimensions for approved outer frames & transom/mullion profiles:								
Multilight Tilt & Turn CS 435 Mullion	1200	1600	-	1550	4	5A	A5	2000

<sup>\*</sup>as given in Table 1 of BS 6375-1:2004

First Issued: 2017-08-09 Latest Issue: 2017-08-09

Page: 3 of 11

No. KM 673813

### BS 4873:2009 - Aluminium Alloy Windows and Doorsets.

This Certificate covers the fabrication of windows from the range of profiles and components supplied by The Parkside Group Ltd under Certificate Number KM 578159.

System(s): **Comar 5Pi Advanced Aluminium Alloy Window System** 

**Fabrication and Installation:** 

Fabricated and installed in accordance with the latest issue(s) of the following

Comar Architectural Aluminium Systems controlled documentation:

Comar 5Pi Advanced Window System Technical Manual

**System description:** The windows are internally glazed only, double glazed only, multipoint locking

only with mechanically fixed transoms/mullions

**Ventilation:** None

**Window Types:** Casement windows

First Issued: 2017-08-09 Latest Issue: 2017-08-09

Page: 4 of 11

No. KM 673813

### **Comar 5Pi Advanced Aluminium Alloy Window System**

### **Size Limitations and Performance characteristics**

Window Type	Width (mm) - Maximum	Height (mm) - Maximum	Area(m²) - Maximum	Transom/Mullion Length (mm) inc frame - Maximum	Air Permeability classification	Watertightness classification	Resistance to Wind classification	Exposure category as given in Table 1 of BS 6375-1:2009	
Sash dimensions for appr	Sash dimensions for approved casement sash profiles:								
Projecting top hungs	1180	1430	-	-	4	9A	A5	2000	

First Issued: 2017-08-09 Latest Issue: 2017-08-09

Page: 5 of 11

No. KM 673813

#### BS 4873:2009 - Aluminium Alloy Windows and Doorsets.

This Certificate covers the fabrication of windows from the range of profiles and components supplied by The Parkside Group Ltd under Certificate Number KM 578159.

System(s): Comar 5Pi ECO 55/75 Aluminium Alloy Window System

**Fabrication and Installation:** 

Fabricated and installed in accordance with the latest issue(s) of the following

Comar Architectural Aluminium Systems controlled documentation:

Comar 5Pi ECO Window System Technical Manual

The windows are internally glazed only, double glazed only, multipoint locking **System description:** 

only with mechanically fixed transoms/mullions

**Ventilation:** None

**Window Types:** Casement windows

Multilight windows comprising opening light(s) and/or fixed light(s)

First Issued: 2017-08-09 Latest Issue: 2017-08-09

Page: 6 of 11

No. KM 673813

### Comar 5Pi ECO 55 & 75 Aluminium Alloy Window System

### **Size Limitations and Performance characteristics**

Window Type	Width (mm) - Maximum	Height (mm) - Maximum	Area(m²) - Maximum	Transom/Mullion Length (mm) inc frame - Maximum	Air Permeability classification	Watertightness classification	Resistance to Wind classification	Exposure category as given in Table 1 of BS 6375-1:2009 (except*)
Sash dimensions for appr	oved case	ment sasi	n profiles:			,	,	
Projecting top hungs	1100	1116	-	-	4	7A	2400	2400*
Overall dimensions for ap	proved ou	iter frame	s & transo	m/mullion	profiles:			
Multilight Projecting side hung next to Projecting side hung Mullion CS 835	1305	1330	-	1270	2	E750	AE	2400
Multilight Projecting side hung next to Fixed Mullion CS 835	1300	1320	-	1235	4	E600	E2400	2400

<sup>\*</sup>as given in Table 1 of BS 6375-1:2004

First Issued: 2017-08-09 Latest Issue: 2017-08-09

Page: 7 of 11

No. KM 673813

### BS 4873:2009 - Aluminium Alloy Windows and Doorsets.

This Certificate covers the fabrication of windows from the range of profiles and components supplied by The Parkside Group Ltd under Certificate Number KM 578159.

System(s): Comar 5Pi ECO+ Aluminium Alloy Window System

**Fabrication and Installation:** 

Fabricated and installed in accordance with the latest issue(s) of the following

Comar Architectural Aluminium Systems controlled documentation:

Comar 5Pi ECO+ Window System Technical Manual

**System description:** The windows are internally glazed only, double glazed only, multipoint locking

only with mechanically fixed transoms/mullions

**Ventilation:** None

**Window Types:** Casement windows

First Issued: 2017-08-09 Latest Issue: 2017-08-09

Page: 8 of 11

No. KM 673813

### Comar 5Pi ECO+ Aluminium Alloy Window System

### **Size Limitations and Performance characteristics**

Window Type	Width (mm) - Maximum	Height (mm) - Maximum	Area(m²) - Maximum	Transom/Mullion Length (mm) inc frame - Maximum	Air Permeability classification	Watertightness classification	Resistance to Wind classification	Exposure category as given in Table 1 of BS 6375-1:2009	
Sash dimensions for appr	Sash dimensions for approved casement sash profiles:								
Projecting top hungs	1152	1152	-	-	4	E750	2400	2400	

First Issued: 2017-08-09 Latest Issue: 2017-08-09

Page: 9 of 11

No. KM 673813

### BS 4873:2009 - Aluminium Alloy Windows and Doorsets.

This Certificate covers the fabrication of windows from the range of profiles and components supplied by The Parkside Group Ltd under Certificate Number KM 578159.

System(s): **Comar 9Pi Aluminium Alloy Window System** 

**Fabrication and Installation:** 

Fabricated and installed in accordance with the latest issue(s) of the following

Comar Architectural Aluminium Systems controlled documentation:

Comar 9Pi Window System Technical Manual

**System description:** The windows are internally glazed only, double glazed only, multipoint locking

only with mechanically fixed transoms/mullions

**Ventilation:** None

**Window Types:** Casement windows

Tilt/turn windows

First Issued: 2017-08-09 Latest Issue: 2017-08-09

Page: 10 of 11

No. KM 673813

#### **Comar 9Pi Aluminium Alloy Window System Size Limitations and Performance characteristics**

Window Type Sash dimensions for appr	Width (mm) - Maximum	Height (mm) - Maximum	Area(m²)	Transom/Mullion Length (mm) inc frame - Maximum	Air Permeability classification	Watertightness classification	Resistance to Wind classification	Exposure category as given in Table 1 of BS 6375-1:2009	
Sasif difficusions for appr	oveu case	1110110 3031	i promes.	I					
Projecting top hungs	995	1595	-	-	4	E900	A5	2000	
Projecting side hungs	1180	1440	-	-	4	9A	AE	2400	
Sash dimensions for appr	Sash dimensions for approved tilt/turn sash profiles:								
Tilt/turns	1180	1440	-	-	4	9A	AE	2400	
Tilt/turns	1040	1650	-	-	4	E750	A5	2000	

First Issued: 2017-08-09 Latest Issue: 2017-08-09

Page: 11 of 11